

APPLICATION FOR ROOFING/ SIDING PERMIT

1. ROOFING: PRESENT ROOFING TYPE PROPOSED

_____	ASPHALT/ FIBERGLASS SHINGLES	_____
_____	SLATE SHINGLES	_____
_____	METAL ROOFING	_____
_____	BUILT-UP ROOFING	_____
_____	WOOD SHINGLES	_____
_____	OTHER	_____

2. ARE YOU STRIPPING THE EXISTING ROOF DOWN TO THE ROOF DECKING?
 YES _____ NO _____

IF YES, ICE AND WATER SHIELD IS REQUIRED 3' UP FROM EDGE OF ROOF.
INITIAL INDICATING THAT THIS WILL BE INSTALLED. _____

3. ARE YOU INSTALLING NEW SHINGLES OVER AN EXISTING ROOF?
 YES _____ NO _____

IF YES, ONLY 1 LAYER OF EXISTING SHINGLES IS PERMITTED UNDER A NEW ROOF COVERING. INITIAL INDICATING ONLY 1 LAYER EXISTS. _____

4. ARE YOU REPLACING ANY STRUCTURAL OR NON-STRUCTURAL MEMBERS?
 (PLYWOOD, RAFTERS, DECKING, SHEATHING, ETC.) YES _____ NO _____

IF YES, LIST MATERIALS REPLACING/USING.

 TOWNHOUSES REQUIRE FIRE RETARDANT PLYWOOD 4' EACH SIDE OF THE PARTYWALL. SHEETS MUST BE INSTALLED STAGGERED (8'4"/8'4' ETC.) CONSTRUCTION PLANS MAY BE REQUIRED DEPENDING ON PROJECT.

5. SIDING/ EXTERIOR VENEER:
A WATER RESISTANT BARRIER IS REQUIRED UNDER SIDINGS, STUCCO, AND STONE/ MASONRY VENEERS.
STUCCO AND 2" STONE VENEER REQUIRES 2 LAYERS OF GRADE "D" PAPER, ALONG WITH A WEEP SCREED AT OR BELOW THE FOUNDATION PLATE LINE. PORTLAND CEMENT PLASTER/ STUCCO SHALL BE A 3 COAT SYSTEM, UNLESS THE PLASTER/ STUCCO IS COVERED WITH A STONE OR OTHER VENEER.

INDICATE TYPE USING _____

<u>PRESENT TYPE</u>		<u>PROPOSED</u>
_____	ALUMINUM/ VINYL	_____
_____	WOOD	_____
_____	CEMENT BOARD	_____
_____	BRICK OR STONE(4"OR MORE THICK)	_____
_____	STUCCO OR STONE VENEER(2"+/- THICK)	_____

ALL WORK TO CONFORM TO THE IRC 2009

OWNER _____ ADDRESS _____ TEL. NO. _____

APPLICANT _____ ADDRESS _____ TEL. NO. _____